

-

Outdoor Commercial Advertising

LED Billboard


CS/serie





Wide view angle

Vertical view 140 degrees and horizontal view 140 degrees to broaden the audience and allow more display of the ad.



High contrast

The unique triple louvre design assists in delivering a perfect image with superb contrast.





Full range of high-end lamp beads and chips sourced to control the stability of the product from the raw material.



Parameters

Pixel Pitch	Unit	4	5	6.6	8	10
Minimum Viewing distance	Meter	4	5	6.6	8	10
LED type	N/A	SMD2727 SMD3535				
Pixel pitch	mm	4	5	6.6	8	10
Brightness	Nits	5500-6500			6500 -7500	
Driving type	Scan	1/10	1/5	1/8	1/4	1/2
Module dimension (WxH)	mm	320 x 320	320 x 320	320 x 320	320 x 320	320 x 320
Cabinet pixel (WxH)	mm	240 * 240	192 * 192	144 * 144	120 * 120	96 * 96
Cabinet material	N/A	Magnesium/Aluminum allloy/Steel				
Maintenance way	N/A	Front/Back				
MAX Power consumption	W/M2	720				
AVG Power consumption	W/M2	240				
Refresh rate	Hz	3840/1920				
Digital processing	Bit	16				
View Angle (H/V)	Degree	140/140				
Gray scale	Level	16384				
Driver IC	N/A	MBI/ICN - PWM				
Ingress protection	N/A	IP67				
Operating Humidity	RH	10 ~ 95%				
Operating Temperature	F/C	-4F~ 140F/ -30 ~ 60				
Life time(50%brightness)	Hrs	100,000				


Maintenance





Solidly-built architecture

The solid structural qualities of the Bibiled standard outdoor cabinets ensure efficient screen performance in the harshest of environments and severe weather conditions.



IP65 water-proof

UV resistant, dustproof and waterproof, IP65 protection level; stable signal and power supply, safe and reliable for outdoor use.



Dual heat dissipation

Low power consumption, low heat, energy saving and environmental protection; excellent thermal design, small attenuation, long life.









Outdoor LED Billboard

Outdoor LED Billboard is the most time-sensitive and flexible form of outdoor advertising. It allows advertisers to connect with audiences in real-time and are an efficient way to work in synergy with other advertising media.

Features



Wide view angle



Solidly-built



High

contrast



Reliable performance





REDLAMP LED

+86 153 9990 6913
Address - The Building C
Tangtou Industrial Park
Shiyan Town, Boan district
Shenzhen

Distributor - UAE

TRICOLOR Al Shaali Building Al Qusais 1, Dubai, UAE 0487 887 19 Pin - 384 912